

ZR81KC-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

<u>Evap(°F)/Cond(°F)</u>	<u>45 / 130</u>	<u>45 / 100</u>
<u>RG(°F)/Liq(°F)</u>	<u>65 / 115</u>	<u>65 / 85</u>
Capacity (Btu/hr)	82000	96500
Power (Watts):	6950	5000
Current (Amps):	20.80	16.30
EER (Btu/Wh):	11.80	19.30
Mass Flow (lbs/hr):	1200	1240
Sound Power (dBA):	75 Avg	80 Max
Vibration (mils(peak- Record Date:	2.0 Avg 2005-08-25	3.0 Max

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	6.58
Bore Size(in):	0.00	Displ(ft ³ /hr):	799.29
Stroke(in):	0.00		
Overall Length (in):	9.48	Mounting Length (in):	7.50
Overall Width (in):	9.71	Mounting Width (in):	7.50
Overall Height (in):	17.95	Mounting Height (in):	18.20 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		3/4 Stub	
Oil Recharge (oz):		56	
Initial Oil Charge (oz):		60	
Net Weight (lbs):		86	
Internal Free Volume (in ³):		258.0	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	164	MCC (Amps):	35.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	26-Jul-1993
LRA Low*:		Max Operating Current:	25.2		
RLA(=MCC/1.4;use for contactor selection):			25		
RLA(=MCC/1.56;use for breaker & wire size)			22.4		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-22 HCFC	50	3	200/220	Air Conditioning