## ZP137KCE-TFD

HFC, R-410A, 60Hz, 3- Phase, 460 V Air Conditioning

## **Production Status:**

Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

	Performance			Med	chanical		
Evap(°F)/Cond(°F)	45 / 130	45 / 100	Number of Cylinde	rs: 0	Displ(in^3/Rev):	7.76	
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0	Bore Size(in): Stroke(in):	0.00 0.00	Displ(ft^3/hr):	942.81	
Capacity (Btu/hr)	135000	168000					
Power (Watts):	12300	8750	Overall Length (in)	: 10.38	Mounting Length (in):	7.50	
Current (Amps):	18.00	13.80	Overall Width (in):	11.23	Mounting Width (in):	7.50	
EER (Btu/Wh):	11.00	19.20	Overall Height (in):	21.00	Mounting Height (in):	21.75	
Mass Flow (lbs/hr):	1990	2070					
			Suction Size (in):		1 3/8 Stub		
Sound Power (dBA):	80 Avg	85 Max	Discharge Size (in)	):	7/8 Stub		
Vibration (mils(peak-	3.0 Avg	4.5 Max	Oil Recharge (oz):		106		
			Initial Oil Charge (	oz):	110		
Record Date:	2005-07-15		Net Weight (lbs):		137		
			Internal Free Volur	ne (in^3):	809.0		
			Horse Power: *Overall compress mounting gromme		Copeland Brand Product	's specified	
		Elect	rical				
LRA-High*:	125.0	MCC (Amps):	29.0	UL File No:	S	A-2337	
LRA-Half Winding:		RPM:	3500	UL File Date:	27-	Sep-1996	
LRA Low*:		Max Operating Current:	25.0				
RLA(=MCC/1.4;use for contactor selection):		20.7					
RLA(=MCC/1.56;use for breaker & wire size		18.6					

Alternate Applications								
Refrigerant	Freq (Hz)	Phase	Voltage	Application				
R-410A HFC	50	3	380/420	Air Conditioning				

